

## Silicon Fiberglass Sleeving

Silicon fiberglass sleeving consists of a silicone Coating, securely bonded to it's supporting fiberglass braid. It is design to remain flexible over wide operating temperature extremes (-75°C to 180°C)

1) Self-extinguish: Yes. 2) Color: White. 3) Length: 50/100 meter per coil.



Size		Wall Thickness mm	Packing Mtr / roll
Inner diameter	Tolerance		
1.0	+ 0.2	0.20 ~ 0.50	100
2.0	+ 0.2	0.23 ~ 0.60	100
3.0	+ 0.2	0.30 ~ 0.70	100
4.0	+ 0.25	0.30 ~ 0.70	100
5.0	+ 0.25	0.30 ~ 0.70	100
6.0	+ 0.25	0.35 ~ 0.70	100
7.0	+ 0.25	0.35 ~ 0.70	100
8.0	+ 0.25	0.37 ~ 1.00	100
9.0	+ 0.5	0.37 ~ 1.00	100
10.0	+ 0.5	0.47 ~ 1.00	100
12.0	+ 0.5	0.55 ~ 1.20	100
14.0	+ 1.0	0.70 ~ 1.50	100
16.0	+ 1.0	0.70 ~ 1.50	50
18.0	+ 1.0	0.70 ~ 1.50	50
20.0	+ 1.0	0.70 ~ 1.50	50
25.0	+ 1.0	0.70 ~ 1.50	50
30.0	+ 1.0	0.70 ~ 1.50	50

## Silicon Rubber Fiberglass Sleeving

Silicon rubber fiberglass sleeving is woven with non-alkali fiberglass yarn, then coated with silicon rubber under high temperature 200°C. With resistant, superior elasticity, cold endurance and antiaging properties. Can be used for the insulating protection of motor and electrical equipment with higher request.

1) Self-extinguish: Yes. 2) Color: Multi 3) Length: 50 / 100 meter per coil.



Size		Wall Thickness mm	Packing Mtr / roll
Inner diameter	Tolerance		
3.0 (Red)	+ 0.2	0.30 ~ 0.70	100
3.0 (White)	+ 0.2	0.30 ~ 0.70	100
7.0 (Red)	+ 0.25	0.37 ~ 1.00	100
7.0 (White)	+ 0.25	0.37 ~ 1.00	100